



REF « VI »

VISITOR

Safety cap overshoe



- Composition: Rubber and protective toe cap in aluminum/titanium
- Professional use : Against impacts and toe crush injuries.
- ✓ Aluminium/titanium toe cap : Ultra light!
- ✓ Velcro comfort strap: 3 sizes to cover from 34 to 50
- ✓ Color code to track sizes
- ✓ Can be adapted to all kind of footwear (even high-heeled shoes)
- ✓ Reusable
- ✓ Tiger-grip® antislip sole with self cleaning studs

Certifications

PPE REGULATION (EU) :
2016/425
(personal protective equipment)



EUROPEAN STANDARDS

CE certification :
0075/1344/161/10/11/0586

- NF EN ISO 20345 / 2011
- NF EN 12568
- Oil resistance (FO)



CE PPE CERTIFIED risk II

Certified organism:
CTC N° 0075/69367 Lyon - France



AMERICAN STANDARDS

- ASTM F 2413-11

● NF EN 12568 – Toe cap resistance

200 joules resistance and resistant to crushing under max. Load of 1500 DaN

Physico-mechanical test			
Test	Standard	VISITOR results	Unit
Shock Resistance	EN ISO 20344	29	mm
Crushing resistance	EN ISO 20344	>30	mm
Traction resistance	ISO 2023: 1994	400	N
Abrasion resistance	ISO 4649: 2002	126	mm ³
Density	ISO 4649:2002	1.20	g/cm ³

Sizes



	S				M				L						
EU Sizes	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48 +
UK Sizes	1	2	3	4	5	6	6,5	7	8	9	10	10,5	11	12	13 +
US Woman	4	5	6	7	7,5	8	8,5	9,5	10	11					
US Man					5,5	6	7	8	8,5	9,5	10	11	11,5	12,5	13 +

For a proper use of the overshoes, it is important to ensure that the overshoes fit neatly over the user's footwear

Storage and maintenance



- Hand washable - Let them dry naturally
- Store in a dry place, away from temperature variation
- Do not use below a temperature of -20°C.

Design and manufacturing: TIGER-GRIP ENGINEERING

✉ contact@tigergrip.com



120, rue Fornier
31700 BEAUZELLE, France



+ 33 5 34 60 56 56

www.tigergrip.com